



FLOOR - wet room

1. Finishing layer

1a Grout (one of the following):

Atlas ARTIS grout	1-25 mm
Atlas TIGHT grout	1-7 mm
Atlas EPOXY grout	1-10 mm
Atlas WIDE grout	4-16 mm
Atlas ARTIS silicone	
Atlas SILTON S silicone	

1b Ceramic tile

2. Adhesive (one of the following):

Atlas GEOFLEX	2-15 mm	C2TE
Atlas ELASTIFIED mortar	2-10 mm	C1TE
Atlas ATUT	2-10 mm	C1T
Atlas MIG2	2-5 mm	C1FTE
Atlas ELASTYK	2-10 mm	C2TE
Atlas PLUS	2-10 mm	C2TES1
Atlas PLUS WHITE	2-10 mm	C2TES1
Atlas PLUS MEGA	4-20 mm	C2E S1
Atlas PLUS MEGA WHITE	4-20 mm	C2E S1
Atlas PLUS EXPRESS	2-5mm	C2FTE S1

3. Under tile waterproof insulation

Woder DUO	Two-component waterproofing
Woder E	Elastic sealing mass
Woder W	Elastic sealing mass

4. Pressure layer - cement screed

Atlas POSTAR 10	thickness up to 100 mm*	CT-C25-F5-A15
Atlas POSTAR 20	thickness up to 80 mm*	CT-C20-F4
Atlas POSTAR 40	thickness up to 80 mm*	CT-C30-F6-A22
Atlas POSTAR 80	thickness up to 80 mm*	CT-C40-F7-A12
Atlas POSTAR 100	thickness up to 80 mm*	CT-C50-F7-A15

5. Protective layer

PE membrane. Recommended thickness: 0.3mm - 0.4 mm

6. Thermal insulation layer

EPS 100 boards or harder thickness acc. thermal calculations
 XPS boards thickness acc. thermal calculations

7. Vapour control membrane

PE membrane (heat-welded or glued)

8. Structural slab

9. Corner profile (aluminum)

10. Sealing tape

Atlas Sealing Tape

Atlas hydroband 3G

11. Threshold trim (aluminum or PCV)

Floor - dry room

A. Finishing layer - parquet

A1 Parquet

A2 Adhesive for parquet

A3 Primer for the adhesive for parquet

B. Pressure layer (screed) according to p.4

C. Protective layer according to p. 5

D. Thermal insulation layer according to p. 6

E. Silicone sealing

Atlas SILIKON ARTIS

Atlas SILTON S

E. ATLAS Backer Rod

*If the floor is arranged in a form of a floating floor, the minimum screed thickness is 40 mm.

No. 3.3.6 Threshold: ceramic floor - parquet