



1. Finishing layer
 - 1a Wooden parquet
 - 1b Adhesive for wooden parquet
2. Primer for the adhesive for wooden parquet
3. Pressure layer - screed

Atlas POSTAR 10	thickness up to 100 mm*	CT-C25-F5-A15
Atlas POSTAR 20	thickness up to 80 mm*	CT-C20-F4
Atlas POSTAR 40	thickness up to 80 mm*	CT-C30-F6-A22
Atlas POSTAR 80	thickness up to 80 mm*	CT-C40-F7-A12
Atlas POSTAR 100	thickness up to 80 mm*	CT-C50-F7-A15
Atlas SAM 150	thickness up to 60 mm*	CA-C20-F5
Atlas SAM 200	thickness up to 60 mm*	CA-C16-F5
Atlas SAM 500	thickness up to 60 mm*	CA-C20-F4
4. Protective layer

PE membrane. Recommended thickness: 0.3 mm - 0.4 mm
5. Thermal insulation layer

EPS 100 boards or harder	thickness acc. thermal calculations
XPS boards	thickness acc. thermal calculations
6. Vapour control membrane

PE membrane (heat-welded or glued)
7. Structural slab
8. Plaster
9. Paint

*If the floor is arranged in a form of a floating floor, the minimum screed thickness is 40 mm.

No. 3.4.6 Floor on a concrete ceiling with parquet flooring without underfloor heating (dry room)