



**1. WALL:**

- concrete or made of ceramic, concrete,  
lime-sand, cellular concrete or stone elements

**2. ADHESIVE FOR POLYSTYRENE:**

- mineral adhesive ATLAS STOPTER K-50  
ATLAS STOPTER K-20  
ATLAS HOTER U  
ATLAS HOTER S

**3. THERMAL INSULATION**

- standard polystyrene slabs (EPS)  
thickness according to thermal calculations

**4. SUPPLEMENTARY MECHANICAL FIXING:**

- mechanical fixings (anchors),  
indicated in the insulation design,  
admitted to trading

**5. BASECOAT:**

- mineral adhesive ATLAS STOPTER K-50  
ATLAS STOPTER K-20  
ATLAS HOTER U

**6. FIBRE-GLASS MESH**

**7. PRIMING MASS (depending on the render type):**

- ATLAS SILKON ANX
- ATLAS CERPLAST

**8. RENDER:**

- ATLAS SILICONE RENDER
- ATLAS SILICATE RENDER
- ATLAS SILICONE-SILICATE RENDER
- ATLAS DEKO M mosaic render
- ATLAS ACRYLIC RENDER
- ATLAS CERMIT N-100 acrylic render
- mineral render: ATLAS CERMIT WN  
ATLAS CERMIT ND  
ATLAS CERMIT MINERAL

**9. PAINT:**

- silicone ATLAS SALTA N  
ATLAS SALTA
- silicate ATLAS SALTA S
- acrylic ATLAS SALTA E
- impregnant ATLAS BEJCA

**dwg no. 1.1.1**

**ATLAS External Wall Insulation System (ETICS)  
based on EPS slabs**