




1. FLOOR PANELS

2. SEPARATING MEMBRANE

3. SOUNDPROOF MEMBRANE

4. PRESSURE LAYER - LEVELLING SCREED *

- Atlas POSTAR 10 40 - 100 mm CT-C25-F5-A12
- Atlas POSTAR 20 40 - 80 mm CT-C20-F4
- Atlas POSTAR 60 40 - 100 mm CT-C30-F5-A9
- Atlas POSTAR 80 40 - 80 mm CT-C40-F7-A9
- Atlas SAM 200 35 - 60 mm CA-C16-F5
- Atlas MMS 60 35 - 60 mm CA-C20-F7
- Atlas SMS 60 ULTRA 30 - 60 mm CT-C25-F-7

5. PROTECTIVE LAYER

PE foil (recommended thickness 0.3-0.4 mm)

6. THERMAL INSULATION LAYER

- EPS boards - type 100 or harder
- XPS boards

7. VAPOUR CONTROL & WATERPROOFING MEMBRANE

- Atlas SMB membrane - thickness 1.5mm

8. PRIMING AGENT: NEXLER DYSPERBIT

9. STRUCTURAL SLAB

10. GEOTEXTILE FABRIC

11. GRAVEL - FILTERING LAYER

12. LEVELLING LAYER / COMPACTED SAND

(*) The thickness of the screed layer in a floating floor system made of a specific product is greater than its nominal minimum thickness.

Follow the instructions in the relevant technical data sheets regarding the correct use of primers.

This drawing is for illustrative purposes only and presents examples of product applications. The suitability of a specific product and its conditions of use should be verified based on the guidelines contained in its technical data sheet.

dwg no. 3.4.2

Floor on the ground
floor panels without underfloor heating