



ATLAS ANTI-ADHESION AGENT

for moulds

- easy and safe to use
- leaves no stains on the substrate
- makes work easier and prevents render from sticking to the mould



Properties

Safe to use - does not contain sulphur or aromatic compounds.

It does not leave stains on textured substrates and is compatible with ATLAS BEJCA.

Easy to apply - no special tools required, excellent working parameters.

It makes working with silicone moulds easier - the agent does not degrade or deform the moulds.

Biodegradable product.

The product is available as a clear red liquid.

Purpose

Preventing mineral renders from adhering to silicone and polyurethane moulds, e.g. in the ATLAS CERMIT WN wood imitation textured render technology - effectively speeds up work and ensures that the desired pattern is achieved without problems.

Technical data

Density	0.91 ÷ 0.92 g/cm ³
Substrate and ambient temperature during the work	from +5 °C to +30 °C
Colour	red

Technical requirements

The primer is not classified as a construction product.

Overlay

Preparation of the measure

ATLAS ANTI-ADHESIVE AGENT is supplied ready for use. It must not be diluted or combined with other materials. Simply shake the container before use to even out the consistency.

Overlay

Apply ATLAS ANTI-ADHESIVE AGENT to the patterned side of the mould with a brush or roller along the mould. Spread the agent thoroughly, covering the surface as uniformly as possible. After the pattern has been rendered twice, brush off any render residue from the mould and reapply a thin layer of anti-adhesion agent.

Consumption

On average, approximately 50 ml is used for a single lubrication of the mould.

Packaging

Plastic container 5 l.

Safety information

Safety information is given on the product packaging and in the Safety Data Sheet, available at www.atlas.com.pl.

Storage and transport

Information on storage and transport is given on the product packaging and in the Safety Data Sheet, available at www.atlas.com.pl.

The shelf life of the product (best before use) is 12 months from the production date on the packaging.

Important additional information

Each time you have finished working, you should wash the silicone mould very thoroughly of any residue of anti-adhesion agent. It is recommended to use water with detergent to wash the mould. Failure to wash the mould thoroughly can result in permanent deformation of the mould and difficulties in obtaining the correct texture.

The information contained in this Technical Data Sheet is a basic guideline for the use of the product and does not relieve the user of the obligation to carry out the work in accordance with the rules of the art of construction and safety regulations. With the issue of this Technical Data Sheet, all previous ones are no longer valid. Documents accompanying the product are available at www.atlas.com.pl.

The contents of the Technical Data Sheet and the designations and trade names used therein are the property of Atlas Ltd. Their unauthorised use will be sanctioned.

Update date: 2022-08-05