

ATLAS ROKER G SYSTEM

set of insulation products

National Technical Assessment ITB-KOT-2018/0583 Edition 2

National Declaration of Performance K005G/2023

National Certificate of Conformity for Factory Production Control No. 020-UWB-0222/Z

ATLAS ROKER G system components

The technology of insulating with the ATLAS ROKER G system consists in attaching mineral wool insulation boards to the surface of internal walls or ceilings (from the side of the ceilings), and then performing an external layer on them according to one of the four material-technology variants.

Purpose of the system	System variation*
Insulating ceilings on the side of ceilings above which heated rooms are located	I, II, IV
Interior insulation of walls in unheated rooms (garages, cellars), enclosed and open spaces with heated rooms nearby	I, II, IV
Insulating the external surfaces of ceilings over passageways, walkways and parking spaces above which heated rooms are located	II

* Insulation with ATLAS ROKER G system, variation I may only be carried out in areas not exposed to mechanical damage.

In the ATLAS ROKER G system, products can be used according to the following list.

VARIETY I - stages of work	Product included in the system variation
thermal insulation	mineral wool (MW) boards in accordance with EN 13162+A1:2015 (plain, lamella and factory primed lamella)
fixing of thermal insulation	ATLAS ROKER U or ATLAS ROKER W mortar + mechanical fasteners
reinforced layer	ATLAS ROKER U mortar + ATLAS 150 or ATLAS 165 glass fibre mesh
Coating	ATLAS SALTA paint ATLAS SALTA S paint ATLAS SALTA N paint

VARIETY II - stages of work	Product included in the system variation
thermal insulation	mineral wool (MW) boards in accordance with EN 13162+A1:2015 (plain, lamella and factory primed lamella)
fixing of thermal insulation	ATLAS ROKER U or ATLAS ROKER W mortar + mechanical fasteners
reinforced layer	ATLAS ROKER U mortar + ATLAS 150 or ATLAS 165 glass fibre mesh
plastering	Thin coat render ATLAS CERMIT ND + primer ATLAS CERPLAST ATLAS SILKON BA + primer ATLAS SILKON ANX or CERPLAST ATLAS SILICONE RENDER - primer ATLAS SILKON ANX or ATLAS CERPLAST ATLAS SILICONE-SILICATE RENDER - Primer ATLAS SILKON ANX or ATLAS CERPLAST
Coating	ATLAS SALTA paint ATLAS SALTA S paint ATLAS SALTA N paint

VARIETY IV - stages of work	Product included in the system variation
thermal insulation	mineral wool lamella panels
fixing of thermal insulation	ATLAS ROKER U or ATLAS ROKER W mortar + mechanical fasteners
Coating	ATLAS SALTA S paint ATLAS SALTA paint

According to the regulations in force, the insulation system is treated as a single construction product in its entirety, and must therefore be used only in the layering and material arrangements described in its technical approval. It is not permissible to use so-called compilations, i.e. the use of products not covered by the technical approval, from other systems or manufacturers.