

Declaration of Performance No

085-2S/1/CPR



Unique identification code of the product-type:	ATLAS FILER S (2022)
Intended use or uses:	In buildings and construction sites
Manufacturer:	ATLAS sp. z o.o. ul. Jana Kilińskiego 2, 91-421 Łódź, Polska telefon: +48 (42) 631 89 45 www.atlas.com.pl
System or systems of assessment and verification of constancy of performance:	System 2+
Harmonized standard:	EN 1504-3:2005 Notified Body No. 1488 Instytut Techniki Budowlanej

Declared performance:

Essential characteristics	Performance
Compressive strength	class R4
Chloride ions content	$\leq 0,05\%$
Adhesion	$\geq 2,0$ MPa
Limited shrinkage/expansion (dimensional stability)	$\geq 1,5$ MPa
Carbonation resistance	Fulfills
Elasticity modulus	≥ 20 GPa
Thermal compatibility	$\geq 2,0$ MPa
Slip resistance	class I i II
Thermal expansion coefficient	NPD
Capillary absorption	$\leq 0,5$ kg/m ² h ^{0,5}
Reaction to fire	A1
Dangerous substances	NPD

The performance of the product is in conformity with the declared performance range. This declaration of performance is issued in accordance to EU Regulation no. 305/2011 under sole responsibility of the manufacturer listed above.

Signed for and on behalf of the manufacturer by: Patrycja Stasiak in Łódź, on 19.07.2022.

ATLAS sp. z o.o.
Dyrektor ds. Jakości
Stasiak
Patrycja Stasiak