



DECORATIVE EFFECT

PEARL ZEN paint is a granular, semi-transparent pearl paint designed for decorative coating of walls and ceilings. Easy to use decorative paint forms effect of pearly depth with slightly dispersed sand which brings elegance and noble appearance to the painted interior. Characterizes with ability for covering of substrate irregularities. Available in 9 ready-to-use colours: coconut cream, natural linen, blue lagoon, sunshine, Bretonian blue, raspberry sorbet, graphite grey, Cassel soil, chocolate bar.

PROPERTIES

PEARL ZEN is manufactured on a basis of acrylic-styrene dispersion in combination with pearly pigments and selected structural additives. Ready to use.

Opaque, single-layer.

Resistant to washing.

Ecological, water-soluble.

Perfect application parameters.

Very short time of effect application.

Quick-drying – dries in approx. 2 hours, allows for room usage just after 12 hours.

USE

PEARL ZEN is designed for forming of decorative effects on plastered walls and ceilings of interior rooms.

Especially recommended for residential housing and public service facilities (offices, service points, shopping malls).

TYPE OF OBJECT	POSSIBILITY OF USE
residential housing	+
public service, educational facilities	+
commercial and service objects	+
industrial buildings	+

PEARL ZEN

decorative structural paint

- structural effect and intensive colours
- decorative, single-coat paint
- 9 ready-to-use effects
- pearl shine
- durable coat finishing



NATURAL
PRODUCT



FOR INDOOR
USE



APPLY WITH
BRUSH

TYPE OF SUBSTRATE	POSSIBILITY OF USE
cement -lime, cement plasters	+
concrete substrates (monolithic and prefabricated)	+
rough walls made of ceramic, silicate hollow blocks, brick, cellular concrete	+
gypsum plasters, top finishes, fillers	+
polymer finishing coat, fillers	+
paper, vinyl, glass fibre wallpapers	+
acrylic painting coats	+

TECHNICAL DATA

Density	approx. 1.1 kg/dm ³
Temperature of paint, substrate and ambient temperature during paint application and drying	from +5 °C up to +25 °C
Number of coats	1
Time of drying	tactile dryness after approx. 2 hours*
Total time of drying (surface use)	approx. 12 hours*
Solvent	dilution of paint is not recommended

Time shown in the table is recommended for application at temperature 20°C and humidity 55%, in lower temperature and higher humidity drying time might be longer.

Maximum content of VOC in the product ≤ 199.9 g/l, maximum allowable VOC content: 200 g/l.



www.fox-dekurator.pl

APPLICATION OF DECORATIVE EFFECT

Substrate preparation

The substrate should be:

- stable,
- air-dry,
- clean – dedusted and cleaned of any old paint coatings or other coats which would impair the paint bonding, in particular of dirt, dust, wax and grease,
- even, free of cracks (gaps should be repaired before painting). It is recommended to use FINITO mass for surface repairs.
- covered with priming paint INITIUM COLOR.

Detailed requirements on substrate preparation.

TYPE OF SUBSTRATE	SUBSTRATE PREPARATION
fresh cement-lime plasters	coating with paint after stabilization (3-4 weeks)
fresh concrete	coating with paint after approx. 1 month since installation
fresh gypsum plasters	coating with paint after stabilization (2 weeks)
old surfaces covered with acrylic or latex paints well bonded to the substrate	no priming – degrease paint by washing with water and detergent and wait until dry
old distempers and other coats poorly bonded to the substrate	remove carefully
old absorbable or dusty substrates	prime e.g. with PRIMER emulsion, coat with base coat paint INITIUM COLOR
substrates infected with fungi	clean and protect with ATLAS MYKOS NO 1 agent

Product preparation

Product is manufactured as ready-to-use, should not be diluted with water. Product should be thoroughly mixed in order to unify the consistency.

Colouring

Product has defined colour range.

Painting

Work should be divided into phases – a single phase is defined as application of product on 1 m² of the surface. Paint should be applied with a brush in a single layer. Paint can be shaped after approx. 2 minutes since application.

Caution: surface can be shaped within 15 minutes. Paint can be shaped with a dry, wide brush (approx. 14 cm wide) with short and soft bristle. Depending on expected effect, brush should be led with parallel, oblique, circular or cross moves. The final decorative effect depends on tools in use and installer's invention.

CONSUMPTION

Average consumption is approx. 0,14 l/m² for 1 coating (1 l of product brings approx. 7 m² of decorative effect).

Actual consumption depends on:

- structure and absorptiveness of the substrate,
- method of the substrate preparation,
- intended decorative effect,
- installer's experience,
- chosen method of application.

PACKAGING

Plastic packaging 1l.

IMPORTANT ADDITIONAL INFORMATION

- Use paint of the same production date on an individual surface or mix the contents of all packages in one container.
- Final effect depends on method of application and the lightning in decorated room.
- Tools must be cleaned with water with detergent directly after use, before the paint dries.
- Keep out of reach of children. Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1). May cause an allergic reaction. Proceed in accordance with the Safety Data Sheet.
- Keep in tightly sealed original and labelled containers, in dry and cool places. Protect against overheating (above 30 °C) and freezing - the product freezes and irreversibly loses its performance at temperature below 0 °C. Protect against direct sunlight. Shelf life in conditions as specified is 24 months from the date of manufacturing shown on the packaging.

The above information constitutes basic guidelines for the application of the product and does not release the user from the obligation of carrying out works according to engineering principles and OHS regulations. At the time of publication of this product data sheet all previous ones become void. Current product technical documentation is available at www.fox-dekorator.pl.

Date of update: 2019-02-06