



Unique identification code of the product-type:	ATLAS CERMIT WN (2019)
Intended use or uses:	Use on external walls, ceilings and columns. Use on internal walls, ceilings, columns and partition walls.
Manufacturer:	ATLAS sp. z o.o. ul. Św. Teresy 105, 91-222 Łódź, Poland telefon: +48 (42) 631 89 45 www.atlas.com.pl
System or systems of assessment and verification of constancy of performance:	System 4
Harmonized standard:	EN 998-1:2016

Declared performance:

Essential characteristics	Performance
Reaction to fire	A1
Water absorption	W_c 1
Water permeability after required seasoning cycles	$\leq 1 \text{ ml/cm}^2$ after 48 h
Water vapour permeability	$\mu \leq 30$
Adhesion after required seasoning cycles	0,3 N/mm ² FP:B
Thermal conductivity/Density	NPD
Durability	NPD
Dangerous substances	NPD

The performance of the product is in conformity with the declared performance range. This declaration of performance is issued in accordance to EU Regulation no. 305/2011 under sole responsibility of the manufacturer listed above.

Signed for and on behalf of the manufacturer by: Patrycja Stasiak in Łódź, 11.06.2021.

ATLAS sp. z o.o.
Dyrektor ds. Jakości
Stasiak
Patrycja Stasiak

.....