



SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ATLAS RESIN AWAY

Creation date	20th September 2019	Version	5.4
Revision date	20th March 2021		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier**
Substance / mixture
UFI
- ATLAS RESIN AWAY
mixture
MJSN-JF67-W61U-0GGH
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**
Mixture's intended use

Main intended use

PC-PNT-OTH Other paints and coating materials

Mixture uses advised against

not available

1.3. Details of the supplier of the safety data sheet

Supplier

Name or trade name	ATLAS sp. z o.o.
Address	ul. Jana Kilińskiego 2, Łódź, 91-421 Poland
VAT Reg No	PL9471936467
Phone	+48 42 631 88 00
E-mail	msds@atlas.com.pl
Web address	www.atlas.com.pl

Competent person responsible for the safety data sheet

Name	ATLAS sp. z o.o.
E-mail	msds@atlas.com.pl

1.4. Emergency telephone number

112 - emergency number
+48 800 168 083 - ATLAS INFOLINE telephone, open from Monday to Friday between 8:00 am - 4:00 pm, other information is answered by the machine.
National Health Service (NHS) 111
National poisoning information centre Scotland, NHS 24: 111

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture**
Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Skin Irrit. 2, H315
Eye Irrit. 2, H319

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse effects on human health and the environment

Causes serious eye irritation. Causes skin irritation.

- 2.2. Label elements**
Hazard pictogram



Signal word
Warning

Hazard statements

H315	Causes skin irritation.
H319	Causes serious eye irritation.



SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ATLAS RESIN AWAY

Creation date 20th September 2019
Revision date 20th March 2021 Version 5.4

Precautionary statements

P102 Keep out of reach of children.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 IF ON SKIN: Wash with plenty of water with soap.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362 Take off contaminated clothing.

Supplemental information

EUH208 Contains Masa poreakcyjna 5-chloro-2-metylo-2H-izotiazol-3-onu i 2-metylo-2H-izotiazol-3-onu (3:1) (CAS: 55965-84-9). May produce an allergic reaction.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Composition in accordance with Regulation EC 684/2004 Contains: Non-ionic surfactants - less than 5% Fragrances - Limonene Phosphates - less than 5% Contains preservatives: Tetramethylglycoluril, Metylchloroisothiazolinone and methylisothiazolinone

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances and additives specified below.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 603-014-00-0	butylglycol	0,5-6	Skin Irrit. 2, H315 Eye Irrit. 2, H319	2, 3
CAS: 1344-09-8 EC: 215-687-4	sodium silicate	2-2,6	Skin Irrit. 2, H315 Eye Irrit. 2, H319	
Index: 603-096-00-8 CAS: 112-34-5 EC: 203-961-6	2-(2-butoxyethoxy)ethanol	0,5-3	Eye Irrit. 2, H319	2, 4
CAS: 15763-76-5 EC: 239-854-6	sodium cumene sulfonate	0,5-2	Eye Irrit. 2, H319	
CAS: 164524-02-1 EC: 629-764-9	Potassium cumene sulfonate	0,5-2	Eye Irrit. 2, H319	
Index: 603-057-00-5	technical benzyl alcohol	0,5-2	Acute Tox. 4, H302+H332 Eye Irrit. 2, H319	
CAS: 5395-50-6 EC: 226-408-0	Tetrahydro-1,3,4,6-tetrakis (hydroxymethyl) imidazo [4,5-d] imidazole-2,5 (1H, 3H) -dione (CAS: 5395-50-6)	0,05-0,1	Skin Sens. 1B, H317	



SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ATLAS RESIN AWAY

Creation date 20th September 2019

Revision date 20th March 2021

Version

5.4

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 613-167-00-5 CAS: 55965-84-9	Reaction mass: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3: 1) (CAS: 55965-84-9)	0-0,00149	Acute Tox. 3, H301 Acute Tox. 2, H310+H330 Skin Corr. 1C, H314 Skin Sens. 1A, H317 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071 Specific concentration limit: Eye Irrit. 2, H319: $0.06\% \leq C < 0.6\%$ Skin Sens. 1A, H317: $C \geq 0.0015\%$ Skin Irrit. 2, H315: $0.06\% \leq C < 0.6\%$ Skin Corr. 1C, H314: $C \geq 0.6\%$ Eye Dam. 1, H318: $C \geq 0.6\%$	1

Notes

- Note B: Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.
- A substance for which exposure limits are set.
- Substance for which biological limit values exist.
- The use of the substance is restricted by Annex XVII of REACH Regulation

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

If swallowed

Rinse out the mouth with water and provide 2-5 dL of water. Provide medical treatment if the person has any health problems.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Not expected.

If on skin

Causes skin irritation.

If in eyes

Causes serious eye irritation.

If swallowed

Irritation, nausea.



SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ATLAS RESIN AWAY

Creation date 20th September 2019
Revision date 20th March 2021 Version 5.4

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in concentrations exceeding the occupational exposure limits. Prevent contact with skin and eyes. Wash hands and exposed parts of the body thoroughly after handling. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in a dedicated, cool, dry and well ventilated place. Storage temperature from + 5 ° C to + 30 ° C. Before use, the product should be mixed.

Content	Packaging type	Material of package
1 kg	bottle	PP

Storage class

12 - Other non-combustible liquids

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union

Commission Directive 2000/39/EC

Substance name (component)	Type	Value	Note
butylglycol	OEL 8 hours	98 mg/m ³	Skin
	OEL 8 hours	20 ppm	



SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ATLAS RESIN AWAY

Creation date 20th September 2019

Revision date 20th March 2021

Version

5.4

European Union

Commission Directive 2000/39/EC

Substance name (component)	Type	Value	Note
butylglycol	OEL 15 minutes	246 mg/m ³	Skin
	OEL 15 minutes	50 ppm	

European Union

Commission Directive 2006/15/EC

Substance name (component)	Type	Value	Note
2-(2-butoxyethoxy)ethanol (CAS: 112-34-5)	OEL 8 hours	67,5 mg/m ³	
	OEL 8 hours	10 ppm	
	OEL 15 minutes	101,2 mg/m ³	
	OEL 15 minutes	15 ppm	

United Kingdom

EH40/2005 Workplace exposure limits (Fourth Edition 2020)

Substance name (component)	Type	Value	Note
butylglycol	WEL 8h	123 mg/m ³	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.
	WEL 8h	25 ppm	
	WEL 15min	246 mg/m ³	
	WEL 15min	50 ppm	
2-(2-butoxyethoxy)ethanol (CAS: 112-34-5)	WEL 8h	67,5 mg/m ³	
	WEL 8h	10 ppm	
	WEL 15min	101,2 mg/m ³	
	WEL 15min	15 ppm	

Biological limit values

United Kingdom

EH40/2005 Workplace exposure limits (Fourth Edition 2020)

Name	Parameter	Value	Tested material	Time of sampling
butylglycol	Butoxyacetic acid	240 mmol/mol creatinine	Urine	End of shift



SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ATLAS RESIN AWAY

Creation date	20th September 2019		
Revision date	20th March 2021	Version	5.4

8.2. Exposure controls

Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

Respiratory protection

Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

Thermal hazard

Data not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	>100 °C
Flammability	non-flammable
Lower and upper explosion limit	not determined
Flash point	not determined
Auto-ignition temperature	not determined
Decomposition temperature	not determined
pH	10-11 (undiluted)
Kinematic viscosity	not determined
Solubility in water	miscible
Partition coefficient n-octanol/water (log value)	1.05 dla alkoholu benzylowego
Vapour pressure	0.022 hPa at 25 °C
Density and/or relative density	
Density	1 g/cm ³
Relative vapour density	not determined
Particle characteristics	not determined
Form	liquid

9.2. Other information

Vapour density	relative to air 3.7 for benzyl alcohol
----------------	--

SECTION 10: Stability and reactivity

10.1. Reactivity

When used in the standard way, there is not any dangerous reaction with other substances.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.



SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ATLAS RESIN AWAY

Creation date	20th September 2019		
Revision date	20th March 2021	Version	5.4

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

Acute toxicity

Based on available data the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met.

Toxicity for specific target organ - single exposure

Based on available data the classification criteria are not met.

Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

Aspiration hazard

Based on available data the classification criteria are not met.

11.2. Information on other hazards

not available

SECTION 12: Ecological information

12.1. Toxicity

not available



SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ATLAS RESIN AWAY

Creation date 20th September 2019
Revision date 20th March 2021 Version 5.4

Acute toxicity

Tetrahydro-1,3,4,6-tetrakis (hydroxymethyl) imidazo [4,5-d] imidazole-2,5 (1H, 3H) -dione (CAS: 5395-50-6)					
Parameter	Method	Value	Exposure time	Species	Environment
EC ₅₀	OECD 202	38.9 mg/l	48 hours	Daphnia (Daphnia magna)	
LC ₅₀	OECD 203	17.6 mg/kg	96 hours	Fish (Oncorhynchus mykiss)	
NOEC	OECD 211	11.2 mg/l	21 days	Other aquatic organisms (Daphnia magna)	
NOEC	OECD 201	3.93 mg/l	72 hours	Algae (Selenastrum capricornutum)	
EC ₅₀	OECD 209	>1000 mg/kg	0,5 hours	Other aquatic organisms	

12.2. Persistence and degradability

not available

Biodegradability

Tetrahydro-1,3,4,6-tetrakis (hydroxymethyl) imidazo [4,5-d] imidazole-2,5 (1H, 3H) -dione (CAS: 5395-50-6)					
Parameter	Method	Value	Exposure time	Environment	Result
	OECD 301A	>70 %			

12.3. Bioaccumulative potential

Data not available.

Tetrahydro-1,3,4,6-tetrakis (hydroxymethyl) imidazo [4,5-d] imidazole-2,5 (1H, 3H) -dione (CAS: 5395-50-6)						
Parameter	Method	Value	Exposure time	Species	Environment	Temperature [°C]
EC ₅₀	OECD 201	8.5 mg/l	72 hours	Other aquatic organisms (Desmodesmus subspicatus)		
BCF	OECD 107	1.41				

12.4. Mobility in soil

Data not available.

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Endocrine disrupting properties

not available

12.7. Other adverse effects

Data not available.

SECTION 13: Disposal considerations



SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ATLAS RESIN AWAY

Creation date	20th September 2019		
Revision date	20th March 2021	Version	5.4

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

07 07 99 wastes not otherwise specified

Packaging waste type code

15 01 02 plastic packaging

SECTION 14: Transport information

14.1. UN number or ID number

not subject to transport regulations

14.2. UN proper shipping name

not relevant

14.3. Transport hazard class(es)

not relevant

14.4. Packing group

not relevant

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

not available

14.7. Maritime transport in bulk according to IMO instruments

not relevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 as amended. Environmental Protection Act 1990 as amended. Clean Air Act 1993 as amended. Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended.



SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ATLAS RESIN AWAY

Creation date 20th September 2019
Revision date 20th March 2021 Version 5.4

Restrictions pursuant to Annex XVII of Regulation (EC) No. 1907/2006 (REACH), as amended

2-(2-butoxyethoxy)ethanol

Restriction	Conditions of restriction
55	1. Shall not be placed on the market for the first time after 27 June 2010, for supply to the general public, as a constituent of spray paints or spray cleaners in aerosol dispensers in concentrations equal to or greater than 3 % by weight. 2. Spray paints and spray cleaners in aerosol dispensers containing DEGBE and not conforming to paragraph 1 shall not be placed on the market for supply to the general public after 27 December 2010. 3. Without prejudice to other Community legislation concerning the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that paints other than spray paints containing DEGBE in concentrations equal to or greater than 3 % by weight of that are placed on the market for supply to the general public are visibly, legibly and indelibly marked by 27 December 2010 as follows: "Do not use in paint spraying equipment".

15.2. Chemical safety assessment

not available

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

H301	Toxic if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H310+H330	Fatal in contact with skin or if inhaled.
H302+H332	Harmful if swallowed or if inhaled.

Guidelines for safe handling used in the safety data sheet

P102	Keep out of reach of children.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water with soap.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing.

A list of additional standard phrases used in the safety data sheet

EUH208	Contains Masa poreakcyjna 5-chloro-2-metylo-2H-izotiazol-3-onu i 2-metylo-2H-izotiazol-3-onu (3:1) (CAS: 55965-84-9). May produce an allergic reaction.
EUH071	Corrosive to the respiratory tract.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures



SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ATLAS RESIN AWAY

Creation date	20th September 2019	Version	5.4
Revision date	20th March 2021		

EC	Identification code for each substance listed in EINECS
EC ₅₀	Concentration of a substance when it is affected 50% of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
EU	European Union
EuPCS	European Product Categorisation System
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
log K _{ow}	Octanol-water partition coefficient
NOEC	No observed effect concentration
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative
Acute Tox.	Acute toxicity
Aquatic Acute	Hazardous to the aquatic environment
Aquatic Chronic	Hazardous to the aquatic environment (chronic)
Eye Dam.	Serious eye damage
Skin Corr.	Skin corrosion
Skin Sens.	Skin sensitization

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.