



ATLAS SZOP

concentrated cement-and-lime residues remover

- for surfaces: resistant to acids, ceramic and stone, chrome-plated, varnished, stainless steel and plastic
- removes rust and water stains



Properties

ATLAS SZOP contains inorganic acid.

It gives the possibility to dilute according to the type and degree of soiling. For example:

coarse, old residues from adhesives, grouts, plastering mortar, etc.	without dilution
deposits from adhesives, grouts, plastering mortar, etc.	1:3 to 1:5
dirt and lime	1:5 to 1:10
rust and tap water stains	1:10 to 1:15

Purpose

Removes cement, lime and gypsum residues - contains inorganic acid and is recommended for cleaning surfaces after construction work where mineral mortars were used.

Removes dirt resulting from usage- dirt, sediment and stains caused by minerals in the water, rust stains, etc.

Types of surfaces to be cleaned - ceramic tiles (glazed tiles, terracotta, porcelain stoneware, clinker) and stone, sanitary facilities, as well as chrome-plated, lacquered and stainless steel and plastic surfaces.

Cleaning

It is recommended that areas soiled with products containing cement or lime are first lightly soaked with water. It is best to use a brush or sponge to apply the preparation to the soiling and to clean the surface afterwards. Depending on the parameters of the substrate, the intensity and type of soiling, the preparation can be applied undiluted or as a water solution (see table). Particularly heavily soiled areas should be soaked with the preparation without dilution and leave it for several minutes for ATLAS SZOP to act. Then you can proceed to remove the dirt. Caution should be exercised when working on surfaces with mortars containing cement or lime, e.g. ceramic cladding whose joints have been filled with cement grout. The use of the product without proper dilution in such a case may mistakenly wash out the mortar or discolour it. In any case, the cleaned surface should be thoroughly washed with clean water or a slightly alkaline water solution.

Consumption

Consumption depends on the degree and nature of soiling.

Packaging

Plastic containers 1 kg.

Safety information

Safety information is given on the product packaging and in the Safety Data Sheet, available at www.atlas.com.pl.

Storage and transport

Information on storage and transport is given on the product packaging and in the Safety Data Sheet, available at www.atlas.com.pl.

The shelf life of the product (best before use) is 36 months from the production date on the packaging.

Important additional information

When cleaning absorbent (porous) surfaces, which allow dirt to penetrate the structure of the material, it can be difficult to remove the dirt.

It is recommended that, prior to the actual application of ATLAS SZOP, a trial application should be made on a less exposed part of the surface to determine the effect of the product on the surface to be cleaned.

Tools should be cleaned with clean water, immediately after use.

The information contained in this Technical Data Sheet is a basic guideline for the use of the product and does not release you from the obligation to carry out the work in accordance with the rules of the art of construction and safety regulations. With the issue of this Technical Data Sheet all previous ones are no longer valid. Documents accompanying the product are available at www.atlas.com.pl.

The contents of the Technical Data Sheet and the designations and trade names used therein are the property of Atlas Ltd. Their unauthorised use will be sanctioned.

Update date: 2022-10-17