

UK Declaration of Conformity no. 213/1-UK/CPR



Unique identification code of the product-type:	ATLAS ELASTYK (2020)
Intended use or uses:	All internal and external tiling.
Manufacturer:	Atlas sp. z o.o. Jana Kilińskiego 2 St., 91-421 Łódź, Poland www.atlas.com.pl
System or systems of AVCP:	System 3
Designated standard:	EN 12004:2007+A1:2012 Approved Body nr 2007 MPA Dresden GmbH Approved Body nr 1614 Politechnika Łódzka

Declared performance:

Essential characteristics	Performance
Reaction to fire	A1 A1 _{fl}
Bond strength expressed as: initial tensile adhesion strength:	$\geq 1.0 \text{ N/mm}^2$
Durability of bond strength against climate/heat ageing action expressed as: tensile adhesion strength after heat ageing	$\geq 1.0 \text{ N/mm}^2$
Durability of bond strength against water/humidity action expressed as: tensile adhesion strength after water immersion	$\geq 1.0 \text{ N/mm}^2$
Durability of bond strength against freeze-thaw cycles expressed as: tensile adhesion strength after freeze-thaw cycles	$\geq 1.0 \text{ N/mm}^2$
Release of dangerous substances	NPD



The performance of the product is in conformity with the declared performance range.

This declaration of performance is issued in accordance to Regulation (EU) 305/2011 as it has effect in the United Kingdom under sole responsibility of the manufacturer listed above.

Signed for and on behalf of the manufacturer by Patrycja Stasiak in Łódź, on 29.02.2024.

ATLAS sp. z o.o.
Dyrektor ds. Jakości
Sboni
Patrycja Stasiak