



Unique identification code of the product-type:	ATLAS PLUS EXPRESS (2019)
Intended use or uses:	Any interior and exterior tiles application
Manufacturer:	ATLAS Sp. z o.o. ul. Św. Teresy 105, 91-222 Łódź phone: (042) 631 89 45 www.atlas.com.pl
System or systems of assessment and verification of constancy of performance:	System 3
Harmonized standard:	PN-EN 12004+A1:2012 (EN 12004:2007+A1:2012) Adhesives for tiles. Requirements, evaluation of conformity, classification and designation Notified certification body No. 0767 MPA Dresden GmbH Notified certification body No. 2007 KIWA Bautest Dresden GmbH

Declared performance:

Essential characteristics	Performance
Class of reaction to fire	A1 A1 _{fl}
Bond strength defined as: - Initial bonding - Early bonding	$\geq 1.0 \text{ N/mm}^2$ $\geq 0.5 \text{ N/mm}^2$
Bond durability in conditioning/thermal ageing conditions defined as: bonding after thermal ageing	$\geq 1.0 \text{ N/mm}^2$
Bond durability in water/damp conditions defined as: bonding after immersion in water	$\geq 1.0 \text{ N/mm}^2$
Bond durability in freeze-thaw cycles conditions defined as: bonding after freeze-thaw cycles	$\geq 1.0 \text{ N/mm}^2$
Release/ content of hazardous substances	NPD

The performance of the product identified above is in conformity with the declared performance range. This declaration of performance is issued in accordance to EU Regulation no. 305/2011 under sole responsibility of the manufacturer listed above.

Signed for and on behalf of the manufacturer by: Patrycja Stasiak in Łódź, on 25.02.2019 (ed. 1)

ATLAS sp. z o.o.
p.o. Dyrektor ds. Jakości

Patrycja Stasiak