

Declaration of Performance no. 167/4/CPR



Unique identification code of the product-type:	ATLAS ZW 330 (2025)
Intended use or uses:	On external walls, ceilings and columns. On walls, ceilings, columns and partitions. EN 13813 CT-C25-F5 Cement-based screed, for interior use In buildings and civil engineering works.
Manufacturer:	Atlas sp. z o.o. Jana Kilińskiego 2 St., 91-421 Łódź, Poland www.atlas.com.pl
System or systems of AVCP:	System 4
Harmonised standard:	EN 998-1:2016 EN 13813:2002 EN 1504-3:2005

Declared performance:

Essential characteristics	Performance
Reaction to fire	A1
Water absorption	W _c 1
Water vapour permeability	μ ≤ 30
Adhesion	0.3 N/mm ² FP:B
Thermal conductivity/Density	NPD
Durability	NPD
Dangerous substances	NPD

Essential characteristics	Performance
Reaction to fire (for direct exposure)	A1 _{fl}
Release of corrosive substances	CT
Water permeability	NPD
Water vapour permeability	NPD
Strength: - Compressive strength - Flexural strength - Wear resistance	C25 F5 NPD
Sound insulation	NPD
Sound absorption	NPD
Thermal resistance	NPD
Chemical resistance	NPD

Declaration of Performance no. 167/4/CPR



Essential characteristics	Performance
Compressive strength	class R2
Chloride ions content	≤ 0,05%
Adhesive bond	NPD
Limited shrinkage/expansion (dimensional stability)	NPD
Carbonation resistance	NPD
Elastic modulus	NPD
Thermal compatibility	NPD
Skid resistance	NPD
Coefficient of Thermal expansion	NPD
Capillary absorption	NPD
Reaction to fire	A1
Dangerous substances	NPD

The performance of the product is in Conformity with the declared performance range. This declaration of performance is issued in accordance to EU Regulation no. 305/2011 under sole responsibility of the manufacturer listed above.

Signed for and on behalf of the manufacturer by Patrycja Stasiak in Łódź, on 14.08.2025.

ATLAS sp. z o.o.
Dyrektor ds. Jakości
Stasiak
Patrycja Stasiak