

# Declaration of Performance no. 1030/1/CPR



|                                                                               |                                                                                                                           |
|-------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Unique identification code of the product-type:                               | ATLAS PLUS BIAŁY (2019)                                                                                                   |
| Intended use or uses:                                                         | All internal and external tiling                                                                                          |
| Manufacturer:                                                                 | Atlas sp. z o.o.<br>Jana Kilińskiego 2 St., 91-421 Łódź, Poland<br><a href="http://www.atlas.com.pl">www.atlas.com.pl</a> |
| System or systems of assessment and verification of constancy of performance: | System 3                                                                                                                  |
| Harmonised standard:                                                          | EN 12004:2007+A1:2012<br>Notified Body no. 0767 MPA Dresden GmbH<br>Notified Body no. 2007 Bautest Dresden GmbH           |

## Declared performance:

| Essential characteristics                                                                                                                                                | Performance               |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|
| Reaction to fire                                                                                                                                                         | A2-s1, d0<br>A2n-s1       |
| Bond strength expressed as: <ul style="list-style-type: none"><li>initial tensile adhesion strength:</li></ul>                                                           | $\geq 1.0 \text{ N/mm}^2$ |
| Durability of bond strength against climate/heat ageing action expressed as: <ul style="list-style-type: none"><li>tensile adhesion strength after heat ageing</li></ul> | $\geq 1.0 \text{ N/mm}^2$ |
| Durability of bond strength against water/humidity action expressed as: <ul style="list-style-type: none"><li>tensile adhesion strength after water immersion</li></ul>  | $\geq 1.0 \text{ N/mm}^2$ |
| Durability of bond strength against freeze-thaw cycles expressed as: <ul style="list-style-type: none"><li>tensile adhesion strength after freeze-thaw cycles</li></ul>  | $\geq 1.0 \text{ N/mm}^2$ |
| Release of dangerous substances                                                                                                                                          | NPD                       |

The performance of the product is in Conformity with the declared performance range. This declaration of performance is issued in accordance to EU Regulation no. 305/2011 under sole responsibility of the manufacturer listed above.

Signed for and on behalf of the manufacturer by Patrycja Stasiak in Łódź, on 23.02.2024.

ATLAS sp. z o.o.  
Dyrektor ds. Jakości  
*Stasiak*  
Patrycja Stasiak