

UK Declaration of Conformity no. E99-UK/CPR



Unique identification code of the product-type:	ATLAS POSTAR 80 (2020)
Intended use or uses:	For internal and external applications. Layers of screed may contain an underfloor heating system. The screed may be used as wearing surface or covered by finishing layer (e.g. ceramic or stone tiles, epoxy screed, fitted carpet, PVC flooring, parquet, floor panels).
Manufacturer:	Atlas sp. z o.o. Jana Kilińskiego 2 St., 91-421 Łódź, Poland tel.: +48 (42) 631 89 45 www.atlas.com.pl
System or systems of assessment and verification of constancy of performance:	System 4
UK Assessment Document	UKAD 190019-00-0502: December 2019
UK Technical Assessment Approved body	ETA-20/0597 from 30/06/2020 Instytut Techniki Budowlanej

Declared performance:

Essential characteristics	Performance
Reaction to fire	A1 _{FL}
Water permeability	NPD
Water vapour permeability	NPD
Compressive strength	C40 (≥ 40 MPa)
Flexural strength	F7 (≥ 7 MPa)
Wear resistance	A9 (≤ 9 cm ³ / 50 cm ²)
Flexural and compressive strength after freeze-thaw cycles, MPa:	
- compressive strength	≥ 40
- flexural strength	≥ 5
Chemical resistance	NPD
Sound insulation	NPD
Sound insulation	NPD
Thermal resistance	NPD



The performance of the product is in conformity with the declared performance range.

This declaration of performance is issued in accordance to Regulation (EU) 305/2011 as it has effect in the United Kingdom under sole responsibility of the manufacturer listed above.

Signed for and on behalf of the manufacturer by Patrycja Stasiak in Łódź, on 29.11.2022.

ATLAS sp. z o.o.
Dyrektor ds. Jakości
Stasiak
Patrycja Stasiak