



ATLAS SZOP 2000

concentrated polymer dispersion residues remover

- for removing soiling from paints, primers and renders
- for natural stone, ceramics, steel, PVC
- for interior and exterior use



FOR INTERIOR
AND EXTERIOR USE
WALL/FLOOR



APPLY WITH
A PAINTBRUSH



APPLY WITH
A SPONGE

Properties

ATLAS SZOP 2000 contains non-ionic surfactants, solvents and alkaline agents.

Works quickly and effectively - contains non-ionic surfactants, solvents and alkaline agents, has the ability to dissolve dispersions quickly.

Dilutable - depending on the degree of soiling, the product can be diluted with water (max. ratio of 1:5).

Purpose

Removes residues from dispersions - stains from priming emulsions (e.g. UNI-GRUNT), protective agents (e.g. DELFIN), emulsion paints, dispersion renders.

Types of surfaces to be cleaned - ceramic tiles (glazed tiles, terracotta, porcelain stoneware, clinker) and stone, sanitary ware, surfaces, chrome-plated, lacquered and made of stainless steel and plastic.

Technical data

Density	approx. 1.0 g/cm ³
Substrate and ambient temperature during the work	from +5 °C to +30 °C

Technical requirements

The cleaner is not classified as a construction product.

Cleaning

Depending on the level of soiling - dilute ATLAS SZOP 2000 with water (max. ratio 1:5) and spread on the surface. Particularly heavily soiled places should be soaked with the liquid without dilution. In any case, leave soaked soiled areas for 15 minutes for the liquid to take effect and then remove the residue using a sharp brush. Repeat if necessary. When the cleaning process is complete, rinse thoroughly with water.

Consumption

Consumption depends on the degree and nature of soiling.

Packaging

Plastic bottles 1 kg.

Safety information

Safety information is given on the product packaging and in the Safety Data Sheet, available at www.atlas.com.pl.

Storage and transport

Information on storage and transport is given on the product packaging and in the Safety Data Sheet, available at www.atlas.com.pl.

The shelf life of the product (best before use) is 12 months from the production date on the packaging.

Important additional information

It is not recommended for cleaning wooden surfaces and glass. If in doubt, a test cleaning of the surface is recommended before proper application.

Tools should be cleaned with clean water, immediately after use.

The information contained in this Technical Data Sheet is a basic guideline for the use of the product and does not release you from the obligation to carry out the work in accordance with the rules of the art of construction and safety regulations. With the issue of this Technical Data Sheet, all previous ones are no longer valid.

The contents of the Technical Data Sheet and the designations and trade names used therein are the property of Atlas Ltd. Their unauthorised use will be sanctioned.

Update date: 2022-12-13