Declaration of Performance no. **229/UK/CPR**

Unique identification code of the product-type:	**ATLAS GEOFLEX EXPRESS (2020)**
Intended use or uses of construction product:	All internal and external tilling
Manufacturer:	Atlas sp. z o.o. Jana Kilińskiego 2 St., 91-421 Łódź, Poland www.atlas.com.pl
System or systems of AVCP:	System 3
Designated standard	EN 12004:2007+A1:2012 Approved Body no. **0767 Kiwa MPA Dresden GmbH** Approved Body no. **1614 Politechnika Łódźka**

Declared performance

Essential characteristics	Performance
Reaction to fire	A1 $A1_{fl}$
Bond strength expressed as: • initial tensile adhesion strength: • early tensile adhesion strength:	 ≥ 1.0 N/mm² ≥ 0.5 N/mm²
Durability of bond strength against climate/heat ageing action expressed as: • tensile adhesion strength after heat ageing	 ≥ 1.0 N/mm²
Durability of bond strength against water/humidity action expressed as: • tensile adhesion strength after water immersion	 ≥ 1.0 N/mm²
Durability of bond strength against freeze-thaw cycles expressed as: • tensile adhesion strength after freeze-thaw cycles	 ≥ 1.0 N/mm²
Release of dangerous substances	NPD

UKCA

The performance of the product is in conformity with the declared performance range.

This declaration of performance is issued in accordance to Regulation (EU) 305/2011 as it has effect in the United Kingdom under sole responsibility of the manufacturer listed above.

Signed for and on behalf of the manufacturer by: Patrycja Stasiak in Łódź, 26.04.2023.

ATLAS sp. z o.o.
Dyrektor ds. Jakości
Patrycja Stasiak

.....