Declaration of Performance no. **194/1/CPR**

Unique identification code of the product-type:	**ATLAS ULTRA GEOFLEX (2019)**
Intended use or uses of construction product:	All internal and external tilling
Manufacturer:	Atlas sp. z o.o. Jana Kilińskiego 2 St., 91-421 Łódź, Poland www.atlas.com.pl
System of assessment and verification of constancy of performance of construction product:	System 3
Harmonised standard	EN 12004:2007+A1:2012 Notified Body **no. 0767 Kiwa MPA Dresden GmbH** Notified Body **no. 1614 Politechnika Łódzka**

Declared performance

Essential characteristics	Performance
Reaction to fire	A1 $A1_{fl}$
Bond strength expressed as: • initial tensile adhesion strength:	≥ 1.0 N/mm²
Durability of bond strength against climate/heat ageing action expressed as: • tensile adhesion strength after heat ageing	≥ 1.0 N/mm²
Durability of bond strength against water/humidity action expressed as: • tensile adhesion strength after water immersion	≥ 1.0 N/mm²
Durability of bond strength against freeze-thaw cycles expressed as: • tensile adhesion strength after freeze-thaw cycles	≥ 1.0 N/mm²
Release of dangerous substances	NPD

The performance of the product is in Conformity with the declared performance range. This declaration of performance is issued in accordance to EU Regulation no. 305/2011 under sole responsibility of the manufacturer listed above

Signed for and on behalf of the manufacturer by: Patrycja Stasiak in Łódź, 29.04.2026.

ATLAS sp. z o.o.
Dyrektor ds. Jakości
Patrycja Stasiak

.....